



## PFA-180

The PFA-180 is the compact & lightweight motorized Fly-Away Antenna solution ideally suited to the worldwide Satellite market. It can be easily transported via IATA weight compliant flight cases by a commercial airline to wherever you need to go and broadcast.

No tools required for PFA-180 installation thanks to its modular design. No special training needed for operator. Only two people make it ready for transmission under 10 minutes. The PFA-180 antenna system is an offset antenna system including 6 segments; 1.8m parabolic reflector, a quick-install feed-arm, feed-horn system and three axes pedestal system. Everything is put in two IATA-compliant rugged boxes.

The precision, accurate reflector surface provides remarkably low side lobes and excellent cross polar performance for the antenna. C, X, Ku and Ka Bands feed-horn system is available.

## Key Features

- User friendly - no need training
- Ready to transmission within ~10 minutes
- Prime Focus Antenna with 6 Segmented 1.8m Reflector
- Aluminium alloy tripod support legs
- High resistance for toughest weather conditions (wind, rain, sun...)
- C, X, Ku and Ka Band options available
- Optional De-Ice



## GENERAL SPECIFICATIONS

Reflector Diameter	1.8m
Reflector Type	Offset
Setup Time	~10 Minutes
Antenna Concept	Prime focus antenna with 6 segmented 1.8m reflector
Number of Cases	3 Cases
Antenna Travels	AZ 360° EL 0° to 85° POL -90° to 90°

## RF CHARACTERISTIC

		Ku-Band	Ka-Band	C-Band	X-Band
Frequency (GHz)	Tx	13.75 - 14.50	17.7 - 21.2	5.850 - 6.725	7.9 - 8.4
	Rx	10.70 - 12.75	27.5 - 31	3.40 - 4.20	7.25 - 7.75
Antenna Gain (±0.2 dBi)	Tx	46,5 (Midband)	51.9+20log(f/29.25)	39,50 (Midband)	41.4+20log(f/8.25)
	Rx	44.8 (Midband)	48.3+20log(f/19.45)	35.40 (Midband)	40.5+20log(f/7.5)
Polarization		Linear	Circular	Linear / Circular	Circular
TX/RX Isolation		85 dB			
Satellite Operator Compliancy		Compliant with most of satellite operator requirements			
VSWR		1.3			
Cross-Polar Rejection		>35 dB within 1 dB beamwidth			
Side Lobe		-14 dB (First Side Lobe)			

## ENVIRONMENTAL SPECIFICATIONS

Temperature	Operational	-30°C to 55°C
	Survival	-40°C to 70°C
Wind Speed	Operational	45 km/h
	Survival	65 km/h
	Operational (with ballast)	80 km/h
	Survival (with ballast)	100 km/h
Rain	Survival in heavy rainstorm	
Humidity	Up to 100% with condensation	

Compliances / Certificates



### TURKEY

**P** : +90 216 540 72 57

**M** : sales@pals.com.tr

**W** : www.pals.com.tr

### NETHERLANDS

**P** : +31 6 85 52 63 16

**M** : sales@pals-comsat.com

**W** : www.pals-comsat.com

