



## PFA-240

Whether you operate in C, X, Ku or Ka band, the PFA-240 could be easily configured to provide instant satellite communications for any application that requires reliable and / or remote connectivity in a rugged environment. It ensures reliable transmission for any applications such as corporate networks, military and emergency communications, etc...

It can be easily transported with IATA weight-compliant flight cases so it can be transport by a commercial airline to wherever you need.

The PFA-240 with light weight, robust 9 segmented Carbon-Fiber main reflector folding feed-arm, fixed sub-reflector facilitates easy and fast installation. Two operators can achieve the installation within 12 minutes without any training and tools requiring.

## Key Features

- Dual offset Carbon-Fiber 9 pieces segmented reflector
- Less than 12 minutes ready to operation with two person
- Easy acquisition without any training and tools
- Fast and high-quality transmission at anytime and anywhere.
- Aluminium alloy tripod support legs
- C, X, Ku and Ka Band options available
- High resistance for toughest weather conditions (wind, rain, sun...)
- Optional De-Ice



## GENERAL SPECIFICATIONS

Reflector Diameter	2.4m	
Reflector Type	Offset	
Setup Time	~12 Minutes	
Antenna Concept	Dual focus antenna with 9 segmented 2.4m main reflector, folding feed-arm, fixed sub-reflector	
Number of Cases	7 Cases	
Antenna Travels	AZ	360°
	EL	0° to 85°
	POL	-90° to 90°

## RF CHARACTERISTIC

		Ku-Band	Ka-Band	C-Band	X-Band
Frequency (GHz)	Tx	13.75 - 14.50	17.7 - 21.2	5.850 - 6.725	7.9 - 8.4
	Rx	10.70 - 12.75	27.5 - 31	3.40 - 4.20	7.25 - 7.75
Antenna Gain (±0.2 dBi)	Tx	48.8 (Midband)	51.7+20log(f/29.25)	41.7 (Midband)	44.0+20log(f/8.25)
	Rx	47.3 (Midband)	48.2+20log(f/19.45)	37.4 (Midband)	43.3+20log(f/7.5)
Polarization		Linear	Circular	Linear / Circular	Circular
TX/RX Isolation		85 dB			
Satellite Operator Compliancy		Compliant with most of satellite operator requirements			
VSWR		1.3			
Cross Polar Rejection		>35 dB within 1 dB beamwidth			
Side Lobe		-14 dB (First Side Lobe)			

## ENVIRONMENTAL SPECIFICATIONS

Temperature	Operational	-30°C to 55°C
	Survival	-40°C to 70°C
Wind Speed	Operational	45 km/h
	Survival	65 km/h
	Operational (with ballast)	80 km/h
	Survival (with ballast)	100 km/h
Rain	Survival in heavy rainstorm	
Humidity	Up to 100% with condensation	

Compliances / Certificates



### TURKEY

**P** : +90 216 540 72 57

**M** : sales@pals.com.tr

**W** : www.pals.com.tr

### NETHERLANDS

**P** : +31 6 85 52 63 16

**M** : sales@pals-comsat.com

**W** : www.pals-comsat.com

